

Toshiba Air Conditioning Data Sheet

RAS-24E2KVG-E
SEIYA (E2) INDOOR UNIT



Model Reference		RAS-B24E2KVG-E	
Nominal	Cooling Capacity	kW	6.5
	Heating Capacity	kW	7.0
	EER/COP	W/W	2.89/3.33
UK	Cooling Total/Sensible	kW	6.35/4.40
	Heating	kW	4.31
Cooling EN14825	Range Min. - Max.	kW	1.7 - 7.2
	Power Input	kW	2.25
	Pdesign	kW	6.5
	SEER/Energy Efficiency Class		6.90/A++
	Seasonal Energy Consumption	kWh/a	330
Heating EN14825	Range Min. - Max.	kW	1.5 - 8.1
	Power Input	kW	2.10
	Pdesign	kW	5.4
	SCOP/Energy Efficiency Class		4.30/A+
	Seasonal Energy Consumption	kWh/a	1757
Air Flow	High - Low	l/s	298 - 185
	High - Low	m ³ /h	1070 - 666
Sound	Pressure High - Low	dB(A)	48 - 29
	Power High	dB(A)	61
Unit	Height x Width x Depth	mm	320x1050x250
	Weight	kg	15
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2" - 1/4"
	Drain Pipe Connection OD/ID	mm	16/14
Remote controller			WH-TG01NE

TOSHIBA

- invisible piping cut-out
- ultra fresh filter
- new remote control
- wireless adapter is supported and can be installed inside the indoor unit
- supports energy monitoring; remote control is connectable with wires and dustless heat exchanger

(Unit : mm)

