

Toshiba Air Conditioning Data Sheet

Ceiling Mount RAV-HM1101CTP-E

Features

- Low noise levels, thanks to high diameter fan and DC motor
- Automatic louvre control for all year round comfort and efficiency
- Suitable for twin/triple/quad connections
- Uses Toshiba TU2C-Link control platform (backward compatible)
- R32 Refrigerant
- Self-cleaning function, enables the air flow to remain constant and fresh and reduces the frequency of service visits
- Infra-red and wired control options available
- Replacement technology' enabling the re-use of existing R410A, R22 or R407C pipework
- Power to outdoor, please see condensing unit sheet for supply requirements



Outdoor Unit		RAV-HM1101CTP-E	
Cooling	Nominal Cooling Capacity	kW	9.5
	UK Cooling Total/Sensible	kW	9.10 / 7.18
	Power Input (rated)	kW	2.95
Energy Efficiency Class	SEER/Energy Efficiency Class		5.28 / A
Heating	Nominal Heating Capacity	kW	11.2
	UK Heating	kW	8.01
	Power Input	kW	2.94
Energy Efficiency Class	SCOP/Energy Efficiency Class		4.19 / A+
Air Flow	High - Low	l/s	517 - 283
	High - Low	m ³ /h	1860 - 1020
Sound	Pressure High - Medium - Low	dB(A)	44 - 38 - 30
	Power High - Medium - Low	dB(A)	57 - 53 - 45
Unit	Height x Width x Depth	mm	235 x 1586 x 690
	Weight	kg	37
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8

The electrical installation needs to meet current UK electrical regulations BS7671:2018+A2:2022 the 18th Edition of the IET regulations. Fuse sizes shown are for guidance only, cables and protective devices should be calculated using the MCA/MOCP details provided

