

## Toshiba Air Conditioning Data Sheet

### Ceiling Mount RAV-HM401CTP-E

#### Features

- Low noise levels, thanks to high diameter fan and DC motor
- Automatic louvre control for all year round comfort and efficiency
- Suitable for twin/triple/quad connections
- Uses Toshiba TU2C-Link control platform (backward compatible)
- R32 Refrigerant
- Self-cleaning function, enables the air flow to remain constant and fresh and reduces the frequency of service visits
- Infra-red and wired control options available
- Replacement technology' enabling the re-use of existing R410A, R22 or R407C pipework
- Power to outdoor, please see condensing unit sheet for supply requirements



Outdoor Unit		RAV-HM401CTP-E	
Cooling	Nominal Cooling Capacity	kW	3.6
	UK Cooling Total/Sensible	kW	3.45 / 2.89
	Power Input (rated)	kW	0.83
Energy Efficiency Class	SEER/Energy Efficiency Class		6.34 / A++
Heating	Nominal Heating Capacity	kW	4.0
	UK Heating	kW	2.56
	Power Input	kW	0.78
Energy Efficiency Class	SCOP/Energy Efficiency Class		5.1 / A+++
Air Flow	High - Low	l/s	250 - 150
	High - Low	m <sup>3</sup> /h	900 - 540
Sound	Pressure High - Medium - Low	dB(A)	37 - 35 - 28
	Power High - Medium - Low	dB(A)	52 - 50 - 43
Unit	Height x Width x Depth	mm	235 x 950 x 690
	Weight	kg	23
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4

The electrical installation needs to meet current UK electrical regulations BS7671:2018+A2:2022 the 18th Edition of the IET regulations. Fuse sizes shown are for guidance only, cables and protective devices should be calculated using the MCA/MOCP details provided

