

Toshiba Air Conditioning Data Sheet

Ceiling Mount RAV-HM561CTP-E

Features

- Low noise levels, thanks to high diameter fan and DC motor
- Automatic louvre control for all year round comfort and efficiency
- Suitable for twin/triple/quad connections
- Uses Toshiba TU2C-Link control platform (backward compatible)
- R32 Refrigerant
- Self-cleaning function, enables the air flow to remain constant and fresh and reduces the frequency of service visits
- Infra-red and wired control options available
- Replacement technology' enabling the re-use of existing R410A, R22 or R407C pipework
- Power to outdoor, please see condensing unit sheet for supply requirements



Outdoor Unit		RAV-HM561CTP-E	
Cooling	Nominal Cooling Capacity	kW	5.0
	UK Cooling Total/Sensible	kW	4.80 / 3.60
	Power Input (rated)	kW	1.61
Energy Efficiency Class	SEER/Energy Efficiency Class		5.28 / A
Heating	Nominal Heating Capacity	kW	5.3
	UK Heating	kW	3.79
	Power Input	kW	1.36
Energy Efficiency Class	SCOP/Energy Efficiency Class		4.08 / A+
Air Flow	High - Low	l/s	250 - 150
	High - Low	m ³ /h	900 - 540
Sound	Pressure High - Medium - Low	dB(A)	37 - 35 - 28
	Power High - Medium - Low	dB(A)	52 - 50 - 43
Unit	Height x Width x Depth	mm	235 x 950 x 690
	Weight	kg	23
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4

The electrical installation needs to meet current UK electrical regulations BS7671:2018+A2:2022 the 18th Edition of the IET regulations. Fuse sizes shown are for guidance only, cables and protective devices should be calculated using the MCA/MOCP details provided

