

Toshiba Air Conditioning Data Sheet

Classic Condensing Unit RAV-GV801ATP-E

Features

- Compact single fan chassis
- Compatible with TU2C-Link control
- Available single and three phase
- Uses Toshiba TU2C-Link control platform (backward compatible)
- R32 Refrigerant
- Power Supply to Outdoor Unit



| Outdoor Unit | | RAV-GV801ATP-E | |
|-------------------------|----------------------------------|-------------------------|-----------------------------|
| Cooling | Nominal Cooling Capacity | kW | 6.7 |
| | Min - Max | kW | 1.5-8.0 |
| Energy Efficiency Class | SEER/Energy Efficiency Class | (Cassette) | 6.00/A+ |
| Heating | Nominal Heating Capacity | kW | 7 |
| | Min - Max | kW | 1.5 - 9.0 |
| Energy Efficiency Class | SCOP/Energy Efficiency Class | (Cassette) | 4.15/A+ |
| Air Flow | Standard Air Flow | m ³ /h - l/s | 2700 - 750 |
| Sound | Pressure Cool - Heat | dB(A) | 48 - 52 |
| | Power Cool - Heat | dB(A) | 65 - 69 |
| Unit | Height x Width x Depth | mm | 550 x 780 x 290 |
| | Weight | kg | 39 |
| Pipe Connection | Flare Connections (gas - liquid) | inch | 5/8 -3/8 |
| Pipe Length | Min - Max - Height (±) | M | 5 - 30 - 20 |
| Refrigerant | Type / kg / TeqCO ₂ | kg | R32 / 1.4 / 0.9 |
| | Charged length / additional | M / g | 20 / 35 |
| Electrical | Power supply/suggested fuse | V/ph/Hz-A | 220-240/1/50, 220/1/60 - 16 |
| | Run current - Max. (Cassette) | Amps | 10.31 |
| | Power outdoor to indoor | | 3 core + earth |

The electrical installation needs to meet current UK electrical regulations BS7671:2018+A2:2022 the 18th Edition of the IET regulations. Fuse sizes shown are for guidance only, cables and protective devices should be calculated using the MCA/MOCP details provided

