

Toshiba Air Conditioning Data Sheet

4-Way Cassette RAV-HM1101UTP-E

Features

- Run/Standby available with U series remote control (rotation/backup)
- Suitable for single/twin connections
- Uses Toshiba TU2C-Link control platform (backward compatible)
- R32 Refrigerant
- Self-cleaning function and Ag-ion tip for anti-mould in drain cap
- Detachable louvre and grille for easy cleaning
- 'Replacement technology' enabling the re-use of existing R410A, R22 or R407C pipework
- Power to outdoor, please see condensing unit sheet for supply requirements



Model Reference		RAV-HM1101UTP-E	
Cooling	Nominal Cooling Capacity	kW	9.5
	UK Cooling Total/Sensible	kW	9.00/7.80
	Power Input (rated)	kW	2.87
Energy Efficiency Class	SEER/Energy Efficiency Class		6.15/A++
Heating	Nominal Heating Capacity	kW	11.2
	UK Heating	kW	5.50
	Power Input	kW	2.93
Energy Efficiency Class	SCOP/Energy Efficiency Class		4.28/A+
Air Flow	High - Medium - Low	l/s	558 - 400 - 325
	High - Medium - Low	m ³ /h	2010 - 1440 - 1170
Sound	Pressure High - Medium - Low	dB(A)	43 - 38 - 33
	Power High - Medium - Low	dB(A)	58 - 53 - 48
Unit	Height x Width x Depth	mm	319 x 840 x 840
	Weight	kg	24
Panel	Height x Width x Depth	mm	30 x 950 x 950
	Weight RBC-U32PGP(W)-E	kg	4.2
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8

The electrical installation needs to meet current UK electrical regulations BS7671:2018+A2:2022 the 18th Edition of the IET regulations. Fuse sizes shown are for guidance only, cables and protective devices should be calculated using the MCA/MOCP details provided

