

## Toshiba Air Conditioning Data Sheet

### 4-Way Cassette RAV-HM1401UTP-E

#### Features

- Run/Standby available with U series remote control (rotation/backup)
- Suitable for single/twin connections
- Uses Toshiba TU2C-Link control platform (backward compatible)
- R32 Refrigerant
- Self-cleaning function and Ag-ion tip for anti-mould in drain cap
- Detachable louvre and grille for easy cleaning
- 'Replacement technology' enabling the re-use of existing R410A, R22 or R407C pipework
- Power to outdoor, please see condensing unit sheet for supply requirements



Model Reference		RAV-HM1401UTP-E	
Cooling	Nominal Cooling Capacity	kW	12.0
	UK Cooling Total/Sensible	kW	11.00/9.30
	Power Input (rated)	kW	4.29
Energy Efficiency Class	SEER/Energy Efficiency Class		5.71/A+
Heating	Nominal Heating Capacity	kW	13.0
	UK Heating	kW	6.55
	Power Input	kW	3.46
Energy Efficiency Class	SCOP/Energy Efficiency Class		4.29/A+
Air Flow	High - Medium - Low	l/s	583 - 400 - 342
	High - Medium - Low	m <sup>3</sup> /h	2100 - 1440 - 1230
Sound	Pressure High - Medium - Low	dB(A)	44 - 38 - 34
	Power High - Medium - Low	dB(A)	59 - 53 - 49
Unit	Height x Width x Depth	mm	319 x 840 x 840
	Weight	kg	24
Panel	Height x Width x Depth	mm	30 x 950 x 950
	Weight RBC-U32PGP(W)-E	kg	4.2
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8

The electrical installation needs to meet current UK electrical regulations BS7671:2018+A2:2022 the 18th Edition of the IET regulations. Fuse sizes shown are for guidance only, cables and protective devices should be calculated using the MCA/MOCP details provided

