

Toshiba Air Conditioning Data Sheet

Wall Mounted RAV-HM401KRTP-E

Features

- Run/Standby available with U series remote control (rotation/backup)
- Self-cleaning feature to prevent mould formation on the heat exchanger coils
- Suitable for single/twin/triple/quad connections
- Uses Toshiba TU2C-Link control platform (backward compatible)
- R32 Refrigerant
- Auto louver mode allows optimum and uniform air distribution
- Wireless remote control with pre-set functions; hi-power mode, quiet mode, comfort sleep, eco-mode
- Replacement technology' enabling the re-use of existing R410A, R22 or R407C pipework
- Power to outdoor, please see condensing unit sheet for supply requirements



Model Reference		RAV-HM401KRTP-E	
Cooling	Nominal Cooling Capacity	kW	3.6
	UK Cooling Total/Sensible	kW	3.42/2.67
	Power Input (rated)	kW	1.13
Energy Efficiency Class (connected to standard DI outdoor)		SEER/Energy Efficiency Class	6.12/A++
Heating	Nominal Heating Capacity	kW	4
	UK Heating	kW	2.86
	Power Input	kW	1.12
Energy Efficiency Class (connected to standard DI outdoor)		SCOP/Energy Efficiency Class	4.22 / A+
Air Flow	High - Medium - Low	l/s	194 - 161 - 125
	High - Medium - Low	m ³ /h	700 - 580 - 450
Sound	Pressure High - Medium - Low	dB(A)	41 - 36 - 30
	Power High - Medium - Low	dB(A)	55 - 51 - 45
Unit	Height x Width x Depth	mm	293 - 798 - 230
	Weight	kg	10
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4

The electrical installation needs to meet current UK electrical regulations BS7671:2018+A2:2022 the 18th Edition of the IET regulations.
Fuse sizes shown are for guidance only, cables and protective devices should be calculated using the MCA/MOCP details provided

