Toshiba Air Conditioning Data Sheet

Wall Mounted RAV-HM801KRTP-E

Features

- Run/Standby available with U series remote control (rotation/backup)
- Self-cleaning feature to prevent mould formation on the heat exchanger coils
- Suitable for single/twin/triple/quad connections
- Uses Toshiba TU2C-Link control platform (backward compatible)
- R32 Refrigerant
- Auto louver mode allows optimum and uniform air distribution
- Wireless remote control with pre-set functions; hi-power mode, quiet mode, comfort sleep, eco-mode
- Replacement technology' enabling the re-use of existing R410A, R22 or R407C pipework
- Power to outdoor, please see condensing unit sheet for supply requirements



Model Reference			RAV-HM801KRTP-E
Cooling	Nominal Cooling Capacity	kW	6.7
	UK Cooling Total/Sensible	kW	6.36/4.66
	Power Input (rated)	kW	2.44
Energy Efficiency Class (connected to standard DI outdoor)	SEER/Energy Efficiency Class		5.73 / A+
Heating	Nominal Heating Capacity	kW	7.7
	UK Heating	kW	5.51
	Power Input	kW	2.61
Energy Efficiency Class (connected to standard DI outdoor)	SCOP/Energy Efficiency Class		4.01/A+
Air Flow	High - Medium - Low	I/s	289 - 253 - 189
	High - Medium - Low	m3/h	1040 - 910 - 680
Sound	Pressure High - Medium - Low	dB(A)	45 - 41 - 35
	Power High - Medium - Low	dB(A)	60 - 56 - 51
Unit	Height x Width x Depth	mm	320 - 1050 - 250
	Weight	kg	14
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 -3/8















