

Toshiba Air Conditioning Data Sheet

4-Way Cassette RAV-HM801UTP-E

Features

- Run/Standby available with U series remote control (rotation/backup)
- Suitable for single/twin/triple/quad connections
- Uses Toshiba TU2C-Link control platform (backward compatible)
- R32 Refrigerant
- Self-cleaning function and Ag-ion tip for anti-mould in drain cap
- Detachable louvre and grille for easy cleaning
- 'Replacement technology' enabling the re-use of existing R410A, R22 or R407C pipework
- Power to outdoor, please see condensing unit sheet for supply requirements



Model Reference		RAV-HM801UTP-E	
Cooling	Nominal Cooling Capacity	kW	6.7
	UK Cooling Total/Sensible	kW	6.40/5.50
	Power Input (rated)	kW	2.20
Energy Efficiency Class	SEER/Energy Efficiency Class		5.81 / A+
Heating	Nominal Heating Capacity	kW	7.7
	UK Heating	kW	3.85
	Power Input	kW	2.13
Energy Efficiency Class	SCOP/Energy Efficiency Class		4.42/A+
Air Flow	High - Medium - Low	l/s	342 - 267 - 225
	High - Medium - Low	m ³ /h	1230 - 960 - 810
Sound	Pressure High - Medium - Low	dB(A)	35 - 31 - 28
	Power High - Medium - Low	dB(A)	50 - 46 - 43
Unit	Height x Width x Depth	mm	256 x 840 x 840
	Weight	kg	20
Panel	Height x Width x Depth	mm	30 x 950 x 950
	Weight RBC-U32PGP(W)-E	kg	4.2
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8

The electrical installation needs to meet current UK electrical regulations BS7671:2018+A2:2022 the 18th Edition of the IET regulations. Fuse sizes shown are for guidance only, cables and protective devices should be calculated using the MCA/MOCP details provided

