

SEIYA: RAS - B07E2KVG-E

- A++ in both Heating and cooling.
- Power supply to indoor or outdoor unit.
- Compatible with WI-FI when utilizing adapter.
- Sleek and compact suitable for all applications.
- Available in both single and multi split applications.



Retail Price (interactive icons):




UK



ROI



Hi - Res Image 

ENTRY TIER PRODUCT RANGE

CODE		20		
Performance				
Indoor Unit		RAS-	B07E2KVG-E	
Outdoor Unit		RAS-	07E2AVG-E	
Nominal	Cooling Capacity	kW	2.0	
	Heating Capacity	kW	2.5	
	EER/COP	W/W	3.77/3.91	
UK	Cooling Total/Sensible	kW	1.95/1.57	
	Heating	kW	1.60	
Cooling EN14825	Range Min. - Max.	kW	0.76 - 2.60	
	Power Input	kW	0.53	
	Pdesign	kW	2.0	
	SEER/Energy Efficiency Class			6.20/A++
	Seasonal Energy Consumption	kWh/a		113
Heating EN14825	Range Min. - Max.	kW	0.82 - 3.30	
	Power Input	kW	0.64	
	Pdesign	kW	2.0	
	SCOP/Energy Efficiency Class			4.60/A++
	Seasonal Energy Consumption	kWh/a		609
Indoor Data				
Air Flow	High - Low	l/s	140 - 55	
	High - Low	m3/h	500 - 200	
Sound	Pressure High - Low	dB(A)	38 - 19	
	Power High - Low	dB(A)	51	
Unit	Height x Width x Depth	mm	288 x 770 x 225	
	Weight	kg	9	
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8" - 1/4"	
	Drain Pipe Connection OD/ID	mm	16/14	
Remote controller			WH-TG01NE	


Accessories

RB-RXS33-E	Option Remote Controller (Weekly Timer)
RB-RXS34-E	Option Black remote
RB-N105S-G	Wireless adapter (Without cable)

*All [Accessories / Controls](#)

Related Items:

- [BIM Files](#)
- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Airflow/ Fan Curve](#)
- [Installation Manual](#)
- [Owners Manual](#)



Cool Designs Ltd

Raising the Standards in Air Conditioning Distribution