

SEIYA: RAS - B10E2KVG-E

- A++ in both Heating and cooling.
- Power supply to indoor or outdoor unit.
- Compatible with Wi-Fi when utilizing adapter.
- Sleek and compact suitable for all applications.
- Available in both single and multi split applications.



Retail Price (interactive icons):




UK



ROI



Hi - Res Image 

ENTRY TIER PRODUCT RANGE

CODE			25	
Performance				
Indoor Unit		RAS-	B10E2KVG-E	
Outdoor Unit		RAS-	10E2AVG-E	
Nominal	Cooling Capacity	kW	2.5	
	Heating Capacity	kW	3.2	
	EER/COP	W/W	3.57/3.72	
UK	Cooling Total/Sensible	kW	2.44/1.93	
	Heating	kW	2.03	
Cooling EN14825	Range Min. - Max.	kW	0.80 - 3.00	
	Power Input	kW	0.70	
	Pdesign	kW	2.5	
	SEER/Energy Efficiency Class			7.00/A++
	Seasonal Energy Consumption	kWh/a		125
Heating EN14825	Range Min. - Max.	kW	0.95 - 3.90	
	Power Input	kW	0.86	
	Pdesign	kW	2.4	
	SCOP/Energy Efficiency Class			4.60/A++
	Seasonal Energy Consumption	kWh/a		730
Indoor Data				
Air Flow	High - Low	l/s	144 - 64	
	High - Low	m3/h	510 - 230	
Sound	Pressure High - Low	dB(A)	39 - 20	
	Power High - Low	dB(A)	52	
Unit	Height x Width x Depth	mm	288 x 770 x 225	
	Weight	kg	9	
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8" - 1/4"	
	Drain Pipe Connection OD/ID	mm	16/14	
Remote controller			WH-TG01NE	

Accessories

RB-RXS33-E	Option Remote Controller (Weekly Timer)
RB-RXS34-E	Option Black remote
RB-N105S-G	Wireless adapter (Without cable)

*All [Accessories / Controls](#)

Related Items:

- [BIM Files](#)
- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Airflow/ Fan Curve](#)
- [Installation Manual](#)
- [Owners Manual](#)

