

SEIYA: RAS - B16E2KVG-E

- A++ in both Heating and cooling.
- Power supply to indoor or outdoor unit.
- Compatible with Wi-Fi when utilizing adapter.
- Sleek and compact suitable for all applications.
- Available in both single and multi split applications.



Retail Price (interactive icons):




UK



ROI



Hi - Res Image 

ENTRY TIER PRODUCT RANGE

CODE		42		
Performance				
Indoor Unit		RAS-	B16E2KVG-E	
Outdoor Unit		RAS-	16E2AVG-E	
Nominal	Cooling Capacity	kW	4.2	
	Heating Capacity	kW	5.0	
	EER/COP	W/W	3.31/3.73	
UK	Cooling Total/Sensible	kW	4.49/3.36	
	Heating	kW	3.33	
Cooling EN14825	Range Min. - Max.	kW	1.40 - 4.70	
	Power Input	kW	1.27	
	Pdesign	kW	4.2	
	SEER/Energy Efficiency Class		7.00/A++	
	Seasonal Energy Consumption	kWh/a	210	
Heating EN14825	Range Min. - Max.	kW	1.30 - 6.00	
	Power Input	kW	1.34	
	Pdesign	kW	3.6	
	SCOP/Energy Efficiency Class		4.60/A++	
	Seasonal Energy Consumption	kWh/a	1095	
Indoor Data				
Air Flow	High - Low	l/s	212 - 92	
	High - Low	m3/h	760 - 330	
Sound	Pressure High - Low	dB(A)	43 - 22	
	Power High - Low	dB(A)	56	
Unit	Height x Width x Depth	mm	293 x 798 x 230	
	Weight	kg	9	
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2" - 1/4"	
	Drain Pipe Connection OD/ID	mm	16/14	
Remote controller			WH-TG01NE	

Accessories

RB-RXS33-E	Option Remote Controller (Weekly Timer)
RB-RXS34-E	Option Black remote
RB-N105S-G	Wireless adapter (Without cable)

*All [Accessories / Controls](#)

Related Items:

- [BIM Files](#)
- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Airflow/ Fan Curve](#)
- [Installation Manual](#)
- [Owners Manual](#)

