

## SEIYA: RAS - B24E2KVG-E

- A++ in both Heating and cooling.
- Power supply to indoor or outdoor unit.
- Compatible with WI-FI when utilizing adapter.
- Sleek and compact suitable for all applications.
- Available in both single and multi split applications.



Retail Price (interactive icons):




UK



ROI



Hi - Res Image 

### ENTRY TIER PRODUCT RANGE

CODE		65		
<b>Performance</b>				
Indoor Unit		RAS-	B24E2KVG-E	
Outdoor Unit		RAS-	24E2AVG-E	
Nominal	Cooling Capacity	kW	6.5	
	Heating Capacity	kW	7.0	
	EER/COP	W/W	2.89/3.33	
UK	Cooling Total/Sensible	kW	6.35/4.40	
	Heating	kW	4.31	
Cooling EN14825	Range Min. - Max.	kW	1.7 - 7.2	
	Power Input	kW	2.25	
	Pdesign	kW	6.5	
	SEER/Energy Efficiency Class			6.90/A++
	Seasonal Energy Consumption	kWh/a		330
Heating EN14825	Range Min. - Max.	kW	1.5 - 8.1	
	Power Input	kW	2.10	
	Pdesign	kW	5.4	
	SCOP/Energy Efficiency Class			4.30/A+
	Seasonal Energy Consumption	kWh/a		1757
<b>Indoor Data</b>				
Air Flow	High - Low	l/s	298 - 183	
	High - Low	m3/h	1070 - 660	
Sound	Pressure High - Low	dB(A)	48 - 29	
	Power High - Low	dB(A)	61	
Unit	Height x Width x Depth	mm	320 x 1050 x 250	
	Weight	kg	15	
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2" - 1/4"	
	Drain Pipe Connection OD/ID	mm	16/14	
Remote controller			WH-TG01NE	

### Accessories

<a href="#">RB-RXS33-E</a>	Option Remote Controller (Weekly Timer)
<a href="#">RB-RXS34-E</a>	Option Black remote
<a href="#">RB-N105S-G</a>	Wireless adapter (Without cable)

\*All [Accessories / Controls](#)

### Related Items:

- [BIM Files](#)
- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Airflow/ Fan Curve](#)
- [Installation Manual](#)
- [Owners Manual](#)

