


## DAISEIKAI 9: RAS - 10PKVPG-E

- Power supply to indoor or outdoor unit.
- 3D Airflow with vertical & horizontal louvres.
- Less than 20dB(A) in silent mode operation.
- Toshiba's leading indoor air quality solution with double filtration system.
- Market Benchmark for High efficiency solutions with A+++ in Heating & Cooling.



Hi - Res Image 

Retail Price (interactive icons):



UK



ROI



### HIGH TIER PRODUCT RANGE

CODE		25	
<b>Performance</b>			
Indoor Unit	RAS-		10PKVPG-E
Outdoor Unit	RAS-		10PAVPG-E
Nominal	Cooling Capacity	kW	2.5
	Heating Capacity	kW	3.2
	EER/COP	W/W	5.56/5.33
UK	Cooling Total/Sensible	kW	2.44/2.03
	Heating	kW	1.90
Cooling EN14825	Range Min. - Max.	kW	0.80 - 3.50
	Power Input	kW	0.45
	Pdesign	kW	2.5
	SEER/Energy Efficiency Class		10.60/A+++
	Seasonal Energy Consumption	kWh/a	83
Heating EN14825	Range Min. - Max.	kW	0.70 - 5.80
	Power Input	kW	0.60
	Pdesign	kW	3.0
	SCOP/Energy Efficiency Class		5.20/A+++
	Seasonal Energy Consumption	kWh/a	807

<b>Indoor Data</b>			
Air Flow	High - Low	l/s	200 - 83
	High - Low	m3/h	720 - 300
Sound	Pressure High - Low	dB(A)	44 - 20
	Power High - Low	dB(A)	58 - 35
Unit	Height x Width x Depth	mm	293 x 851 x 270
	Weight	kg	14
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8" - 1/4"
	Drain Pipe Connection OD/ID	mm	16/14
Remote controller			WH-TA01LE

### Accessories

[RB-N105S-G](#) Wireless adapter (Without cable)

\*All [Accessories / Controls](#)

### Related Items:

- [BIM Files](#)
- [CAD Files](#)
- [Airflow/ Fan Curve](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Installation Manual](#)
- [Owners Manual](#)



### -1. Indoor Unit

