


DAISEIKAI 9: RAS - 16PKVPG-E

- Power supply to indoor or outdoor unit.
- 3D Airflow with vertical & horizontal louvres.
- Less than 20dB(A) in silent mode operation.
- Toshiba's leading indoor air quality solution with double filtration system.
- Market Benchmark for High efficiency solutions with A+++ in Heating & Cooling.



Hi - Res Image 

Retail Price (interactive icons):



UK



ROI



HIGH TIER PRODUCT RANGE

CODE		45	
Performance			
Indoor Unit		RAS-	16PKVPG-E
Outdoor Unit		RAS-	16PAVPG-E
Nominal	Cooling Capacity	kW	4.5
	Heating Capacity	kW	5.5
	EER/COP	W/W	4.17/4.01
UK	Cooling Total/Sensible	kW	4.40/3.56
	Heating	kW	3.43
Cooling EN14825	Range Min. - Max.	kW	0.90 - 5.10
	Power Input	kW	1.08
	Pdesign	kW	4.5
	SEER/Energy Efficiency Class		8.50/A+++
	Seasonal Energy Consumption	kWh/a	185
Heating EN14825	Range Min. - Max.	kW	0.80 - 6.80
	Power Input	kW	1.37
	Pdesign	kW	4.5
	SCOP/Energy Efficiency Class		4.60/A++
	Seasonal Energy Consumption	kWh/a	1369
Indoor Data			
Air Flow	High - Low	l/s	206 - 86
	High - Low	m3/h	740 - 310
Sound	Pressure High - Low	dB(A)	46 - 22
	Power High - Low	dB(A)	60 - 37
Unit	Height x Width x Depth	mm	293 x 851 x 270
	Weight	kg	14
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2" - 1/4"
	Drain Pipe Connection OD/ID	mm	16/14
Remote controller			WH-TA01LE

Accessories

[RB-N105S-G](#) Wireless adapter (Without cable)

*All [Accessories / Controls](#)

Related Items:

- [BIM Files](#)
- [CAD Files](#)
- [Airflow/ Fan Curve](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Installation Manual](#)
- [Owners Manual](#)



-1. Indoor Unit

