

DAISEIKAI 9: RAS - 10PAVPG-E - 16PAVPG-E

- Outdoor unit noise reduction at night.
- Power supply to indoor or outdoor unit
- Capacity booster to reach comfort set point faster.
- Energy Class A+++/A+++ cooling and heating modes.
- Wide ambient range: cooling -15°C to 46°C heating -15°C to 24°C.



Hi - Res Image

Retail Price (interactive icons):



UK



ROI



HIGH TIER PRODUCT RANGE

CODE			25	35	45
Performance					
Outdoor Unit		RAS-	10PAVPG-E	13PAVPG-E	16PAVPG-E
Operating Range	Cooling	C°	-15 ~ 46	-15 ~ 46	-15 ~ 46
	Heating		-15 ~ 24	-15 ~ 24	-15 ~ 24
Air Flow	High	m3/h - l/s	2160 - 600	2160 - 600	2160 - 600
Sound	Pressure High Cooling/Heating/Silent	dB(A)	46 / 47 / 42	48 / 50 / 45	49 / 50 / 45
	Power High Cooling/Heating/Silent	dB(A)	61 / 62 / 57	63 / 65 / 60	64 / 65 / 60
Unit	Height x Width x Depth	mm	630 x 800 x 300	630 x 800 x 300	630 x 800 x 300
	Weight	kg	38	38	38
Pipe Connection	Flare Connections (gas-liquid)	inch	3/8" - 1/4"	3/8" - 1/4"	1/2" - 1/4"
	Min.-Max. Length	m	2-25	2-25	2-25
	Maximum Height Difference	m	±10	±10	±10
	Drain Port Connection	mm	16	16	16
Refrigerant Charge	Base Charge/Chargeless Length	m	1.0/15	1.0/15	1.0/15
	Additional Charge	g/m	20	20	20
Run Current	Maximum	Amps	3.40	4.01	6.44
Power Cable	Outdoor to Indoor		3 core + earth	3 core + earth	3 core + earth
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-10	220-240/1/50-10	220-240/1/50-16

Related Items - 10PAVPG-E:

- [BIM Files](#)
- [CAD Files](#)
- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Noise Curve Data](#)
- [Installation Manual](#)



Related Items - 13PAVPG-E:

- [BIM Files](#)
- [CAD Files](#)
- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Noise Curve Data](#)
- [Installation Manual](#)



Related Items - 16PAVPG-E:

- [BIM Files](#)
- [CAD Files](#)
- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Noise Curve Data](#)
- [Installation Manual](#)



*All [Accessories / Controls](#)

