

DAISEIKAI 10: RAS - B10S4KV*G-E

- Power supply to indoor or outdoor unit.
- WI-FI built in with advanced energy monitoring.
- New smart sensing with thermo mapping technology.
- Provides outstanding performance even down to temperatures of -30°C.
- Daiseikai 10 epitomises reliability and durability with sustainability at its core.



Hi - Res Image

Retail Price (interactive icons):

- UK ROI WOOD
 UK ROI WHITE



ELITE TIER PRODUCT RANGE

CODE		25	
Performance			
Indoor Unit	White	RAS-	B10S4KVPG-E
Indoor Unit	Wood	RAS-	B10S4KVDG-E
Outdoor Unit		RAS-	10S4AVPG-E
Nominal	Cooling Capacity	kW	2.5
	Heating Capacity	kW	3.2
	EER/COP	W/W	5.32/5.33
UK	Cooling Total/Sensible	kW	2.44/2.03
	Heating	kW	1.90
Cooling EN14825	Range Min. - Max.	kW	0.60 - 3.50
	Power Input	kW	0.47
	Pdesign	kW	2.5
	SEER/Energy Efficiency Class		10.70/A+++
Heating EN14825	Seasonal Energy Consumption	kWh/a	82
	Range Min. - Max.	kW	0.65 - 5.80
	Power Input	kW	0.60
	Pdesign	kW	3.0
	SCOP/Energy Efficiency Class		5.30/A+++
Seasonal Energy Consumption	kWh/a	792	
Indoor Data			
Air Flow	High - Low	l/s	208 - 83
	High - Low	m3/h	750 - 300
Sound	Pressure High - Low	dB(A)	41 - 25
	Power High - Low	dB(A)	55 - 40
Unit	Height x Width x Depth (White)	mm	293 x 930 x 255
	Height x Width x Depth (Wood)	mm	293 x 940 x 257
	Weight (White/Wood)	kg	14/16
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8" - 1/4"
	Drain Pipe Connection OD/ID	mm	16/14
Remote controller	White		WH-UD02UE
Remote controller	Wood		WH-UD01UE

Related Items - WOOD:

- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)



Related Items - WHITE:

- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Installation Manual](#)

