

## DAISEIKAI 10: RAS - B13S4KVPG-E

- Power supply to indoor or outdoor unit.
- Wi-Fi built in with advanced energy monitoring.
- New smart sensing with thermo mapping technology.
- Provides outstanding performance even down to temperatures of -30°C.
- Daiseikai 10 epitomises reliability and durability with sustainability at its core.



Retail Price (interactive icons):

- UK ROI WOOD  
 UK ROI WHITE



Hi - Res Image

### ELITE TIER PRODUCT RANGE

CODE		35	
<b>Performance</b>			
Indoor Unit	White	RAS-	B13S4KVPG-E
Indoor Unit	Wood	RAS-	B13S4KVDG-E
Outdoor Unit		RAS-	<a href="#">13S4AVPG-E</a>
Nominal	Cooling Capacity	kW	3.5
	Heating Capacity	kW	4.0
	EER/COP	W/W	4.38/5.00
UK	Cooling Total/Sensible	kW	3.42/2.74
	Heating	kW	2.51
Cooling EN14825	Range Min. - Max.	kW	0.90 - 4.20
	Power Input	kW	0.80
	Pdesign	kW	3.5
	SEER/Energy Efficiency Class		9.70/A+++
Heating EN14825	Seasonal Energy Consumption	kWh/a	126
	Range Min. - Max.	kW	0.70 - 6.30
	Power Input	kW	.80
	Pdesign	kW	3.6
	SCOP/Energy Efficiency Class		5.20/A+++
	Seasonal Energy Consumption	kWh/a	969
<b>Indoor Data</b>			
Air Flow	High - Low	l/s	222 - 91
	High - Low	m3/h	800 - 330
Sound	Pressure High - Low	dB(A)	42 - 26
	Power High - Low	dB(A)	57 - 41
Unit	Height x Width x Depth (White)	mm	293 x 930 x 255
	Height x Width x Depth (Wood)	mm	293 x 940 x 257
	Weight (White/Wood)	kg	14/16
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8" - 1/4"
	Drain Pipe Connection OD/ID	mm	16/14
Remote controller	White		WH-UD02UE
Remote controller	Wood		WH-UD01UE

### Related Items - WOOD:

- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)



### Related Items - WHITE:

- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Installation Manual](#)

