

DAISEIKAI 10: RAS - B18S4KVPGE

- Power supply to indoor or outdoor unit.
- Wi-Fi built in with advanced energy monitoring.
- New smart sensing with thermo mapping technology.
- Provides outstanding performance even down to temperatures of -30°C.
- Daiseikai 10 epitomises reliability and durability with sustainability at its core.



Hi - Res Image



Retail Price (interactive icons):

- UK ROI WOOD
 UK ROI WHITE

ELITE TIER PRODUCT RANGE

CODE		25	
Performance			
Indoor Unit	White	RAS-	B18S4KVPGE
Indoor Unit	Wood	RAS-	B18S4KVDGE
Outdoor Unit		RAS-	18S4AVPG-E
Nominal	Cooling Capacity	kW	5.0
	Heating Capacity	kW	6.0
	EER/COP	W/W	3.57/4.14
UK	Cooling Total/Sensible	kW	4.40/3.56
	Heating	kW	3.43
Cooling EN14825	Range Min. - Max.	kW	0.90 - 6.0
	Power Input	kW	1.40
	Pdesign	kW	5.0
	SEER/Energy Efficiency Class		8.60/A+++
	Seasonal Energy Consumption	kWh/a	203
Heating EN14825	Range Min. - Max.	kW	0.80 - 7.20
	Power Input	kW	1.45
	Pdesign	kW	4.5
	SCOP/Energy Efficiency Class		4.80/A++
	Seasonal Energy Consumption	kWh/a	1312
Indoor Data			
Air Flow	High - Low	l/s	225 - 2
	High - Low	m3/h	810 - 37
Sound	Pressure High - Low	dB(A)	45 - 26
	Power High - Low	dB(A)	59 - 41
Unit	Height x Width x Depth (White)	mm	293 x 930 x 255
	Height x Width x Depth (Wood)	mm	293 x 940 x 257
	Weight (White/Wood)	kg	14/16
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2" - 1/4"
	Drain Pipe Connection OD/ID	mm	16/14
Remote controller	White		WH-UD02UE
Remote controller	Wood		WH-UD01UE

Related Items - WOOD:

- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)



Related Items - WHITE:

- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)

