

## COMPACT CASSETTE: RAS - M16U2MUVG-E

- Optional Occupancy sensor.
- Optional wired remote controller.
- Optional Wireless remote controller kit.
- Elegant and unobtrusive with modern design.
- Suited for 600x600 grid ceilings thanks to compact and thin chassis.



Retail Price (interactive icons):




UK



ROI



Hi - Res Image 

CODE			45
<b>Performance</b>			
<b>Indoor Unit</b>		RAS-	M16U2MUVG-E
Capacity Code			16
Nominal	Cooling Capacity	kW	4.5
	Heating Capacity	kW	5.5
UK	Cooling Total/Sensible	kW	4.49/3.56
	Heating	kW	3.53
Cooling EN14825	Range Min. - Max.	kW	2.13 - 4.50
	Power Input	kW	0.023
Heating EN14825	Range Min. - Max.	kW	2.33 - 5.50
	Power Input	kW	0.023
<b>Indoor Data</b>			
Air Flow	High - Low	l/s	189 - 125
	High - Low	m <sup>3</sup> /h	680 - 450
Sound	Pressure High - Low	dB(A)	40 - 31
	Power High - Low	dB(A)	55 - 46
Unit	Height x Width x Depth	mm	256 x 575 x 575
	Weight	kg	15
Panel RBC-UM21PG(W)-E	Height x Width x Depth	mm	12 x 620 x 620
	Weight	kg	3
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	32/25

### Accessories

<a href="#">RBC-AX32UM(W)-E</a>	Wireless remote controller Kit
<a href="#">RB-RWS21-E</a>	Wired Remote Controller
<a href="#">TCB-SIR41UM-E</a>	Occupancy sensor

\*All [Accessories / Controls](#)

### Related Items:

- [BIM Files](#)
- [CAD Files](#)
- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Airflow/ Fan Curve](#)
- [Noise Curve Data](#)
- [Installation Manual](#)
- [Owners Manual](#)

