


DUCTED: RAS - M07U2DVG-E

- Slim design with only 210mm height.
- External static pressure from 10 to 45 Pa.
- Compatible with latest R32 Multi System.
- Inbuilt Condensate drain pump with lift up to 350mm.
- Compliant with European Ecodesign regulation - Lot10.



Retail Price (interactive icons):




UK



ROI



Hi - Res Image 

CODE		20	
Performance			
Indoor Unit		RAS-	M07U2DVG-E
Capacity Code			7
Nominal	Cooling Capacity	kW	2.0
	Heating Capacity	kW	2.7
UK	Cooling Total/Sensible	kW	1.95/1.57
	Heating	kW	1.60
Cooling EN14825	Range Min. - Max.	kW	1.01 - 2.03
	Power Input	kW	0.048
Heating EN14825	Range Min. - Max.	kW	1.23 - 2.95
	Power Input	kW	0.048
Indoor Data			
Air Flow	High - Low	l/s	158 - 106
	High - Low	m3/h	570 - 380
External Static Pressure	Standard (Upper - Lower)	Pa	10 (10 - 45)
Sound Pressure	High - Low	dB(A)	35 - 27
	High - Low (under inlet)	dB(A)	44 - 30
Sound Power	High - Low	dB(A)	50 - 42
	High - Low (under inlet)	dB(A)	59 - 45
Unit	Height x Width x Depth	mm	210 x 700 x 450
	Weight	kg	16
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4
	Drain Pipe Connection OD/ID	mm	32/25
Remote Controller			WH-TA04NE

Accessories

[RB-RWS21-E](#) | Wired Remote Controller

*All [Accessories / Controls](#)

Related Items:

- [BIM Files](#)
- [CAD Files](#)
- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Airflow/ Fan Curve](#)
- [Noise Curve Data](#)
- [Installation Manual](#)
- [Owners Manual](#)

