


SLIM DUCTED: RAS - M13U2DVG-E

- Slim design with only 210mm height.
- External static pressure from 10 to 45 Pa.
- Compatible with latest R32 Multi System.
- Inbuilt Condensate drain pump with lift up to 350mm.
- Compliant with European Ecodesign regulation - Lot10.



Retail Price (interactive icons):




UK



ROI



Hi - Res Image 

CODE		37	
Performance			
Indoor Unit		RAS-	M13U2DVG-E
Capacity Code			13
Nominal	Cooling Capacity	kW	3.7
	Heating Capacity	kW	5.0
UK	Cooling Total/Sensible	kW	3.22/2.49
	Heating	kW	2.20
Cooling EN14825	Range Min. - Max.	kW	1.71 - 3.70
	Power Input	kW	0.054
Heating EN14825	Range Min. - Max.	kW	2.07 - 5.00
	Power Input	kW	0.054
Indoor Data			
Air Flow	High - Low	l/s	169 - 107
	High - Low	m3/h	610 - 385
External Static Pressure	Standard (Upper - Lower)	Pa	10 (10 - 45)
Sound Pressure	High - Low	dB(A)	37 - 27
	High - Low (under inlet)	dB(A)	46 - 30
Sound Power	High - Low	dB(A)	52 - 42
	High - Low (under inlet)	dB(A)	61 - 45
Unit	Height x Width x Depth	mm	210 x 700 x 450
	Weight	kg	16
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4
	Drain Pipe Connection OD/ID	mm	32/25
Remote Controller			WH-TA04NE

Accessories

[RB-RWS21-E](#) | Wired Remote Controller

*All [Accessories / Controls](#)

Related Items:

- [BIM Files](#)
- [CAD Files](#)
- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Airflow/ Fan Curve](#)
- [Noise Curve Data](#)
- [Installation Manual](#)
- [Owners Manual](#)

