


## SLIM DUCTED: RAS - M22U2DVG-E

- Slim design with only 210mm height.
- External static pressure from 10 to 45 Pa.
- Compatible with latest R32 Multi System.
- Inbuilt Condensate drain pump with lift up to 350mm.
- Compliant with European Ecodesign regulation - Lot10.



Retail Price (interactive icons):




UK



ROI



Hi - Res Image 

CODE		60	
<b>Performance</b>			
<b>Indoor Unit</b>		<b>RAS-</b>	<b>M22U2DVG-E</b>
Capacity Code			22
Nominal	Cooling Capacity	kW	6.0
	Heating Capacity	kW	7.0
UK	Cooling Total/Sensible	kW	5.96/4.24
	Heating	kW	3.98
Cooling EN14825	Range Min. - Max.	kW	2.93 - 6.00
	Power Input	kW	0.069
Heating EN14825	Range Min. - Max.	kW	3.04 - 7.00
	Power Input	kW	0.069
<b>Indoor Data</b>			
Air Flow	High - Low	l/s	278 - 206
	High - Low	m3/h	1000 - 740
External Static Pressure	Standard (Upper - Lower)	Pa	10 (10 - 45)
Sound Pressure	High - Low	dB(A)	38 - 32
	High - Low (under inlet)	dB(A)	45 - 37
Sound Power	High - Low	dB(A)	53 - 47
	High - Low (under inlet)	dB(A)	60 - 52
Unit	Height x Width x Depth	mm	210 x 1100 x 450
	Weight	kg	22
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	32/25
Remote Controller			WH-TA04NE

### Accessories

[RB-RWS21-E](#) | Wired Remote Controller

\*All [Accessories / Controls](#)

### Related Items:

- [BIM Files](#)
- [CAD Files](#)
- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Airflow/ Fan Curve](#)
- [Noise Curve Data](#)
- [Installation Manual](#)
- [Owners Manual](#)

