


SLIM DUCTED: RAS - M24U2DVG-E

- Slim design with only 210mm height.
- External static pressure from 10 to 45 Pa.
- Compatible with latest R32 Multi System.
- Inbuilt Condensate drain pump with lift up to 350mm.
- Compliant with European Ecodesign regulation - Lot10.



Retail Price (interactive icons):




UK



ROI



Hi - Res Image 

| CODE | | | 71 |
|--------------------------|----------------------------------|-------------|-------------------|
| Performance | | | |
| Indoor Unit | | RAS- | M24U2DVG-E |
| Capacity Code | | | 24 |
| Nominal | Cooling Capacity | kW | 7.1 |
| | Heating Capacity | kW | 8.1 |
| UK | Cooling Total/Sensible | kW | 6.84/4.71 |
| | Heating | kW | 5.27 |
| Cooling EN14825 | Range Min. - Max. | kW | 3.28 - 7.10 |
| | Power Input | kW | 0.076 |
| Heating EN14825 | Range Min. - Max. | kW | 3.36 - 8.10 |
| | Power Input | kW | 0.076 |
| Indoor Data | | | |
| Air Flow | High - Low | l/s | 294 - 211 |
| | High - Low | m3/h | 1060 - 760 |
| External Static Pressure | Standard (Upper - Lower) | Pa | 10 (10 - 45) |
| Sound Pressure | High - Low | dB(A) | 39 - 33 |
| | High - Low (under inlet) | dB(A) | 46 - 38 |
| Sound Power | High - Low | dB(A) | 54 - 48 |
| | High - Low (under inlet) | dB(A) | 61 - 53 |
| Unit | Height x Width x Depth | mm | 210 x 1100 x 450 |
| | Weight | kg | 22 |
| Pipe Connection | Flare Connections (gas - liquid) | inch | 1/2 - 1/4 |
| | Drain Pipe Connection OD/ID | mm | 32/25 |
| Remote Controller | | | WH-TA04NE |

Accessories

[RB-RWS21-E](#)

Wired Remote Controller

*All [Accessories / Controls](#)

Related Items:

- [BIM Files](#)
- [CAD Files](#)
- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Airflow/ Fan Curve](#)
- [Noise Curve Data](#)
- [Installation Manual](#)
- [Owners Manual](#)

