


BI-FLOW: RAS - B13J2FVG-E

- Easily blends into any decor.
- Wi-Fi available when utilising adapter.
- Compact design suitable for under window ledges.
- Floor mounted design to ensure perfect air distribution.
- Provides optimum comfort with A++ in heating and cooling.



Hi - Res Image 

Retail Price (interactive icons):



UK



ROI



CODE		35	
Performance			
Indoor Unit		RAS-	B13J2FVG-E
Outdoor Unit		RAS-	13J2AVSG-E1
Nominal	Cooling Capacity	kW	3.5
	Heating Capacity	kW	4.2
	EER/COP	W/W	4.02/3.31
UK	Cooling Total/Sensible	kW	3.42/2.74
	Heating	kW	2.51
Cooling EN14825	Range Min. - Max.	kW	1.05 - 4.1
	Power Input	kW	0.87
	Pdesign	kW	3.5
	SEER/Energy Efficiency Class		7.00/A++
	Seasonal Energy Consumption	kWh/a	174
Heating EN14825	Range Min. - Max.	kW	1.0 - 5.0
	Power Input	kW	1.27
	Pdesign	kW	3.0
	SCOP/Energy Efficiency Class		4.70/A++
	Seasonal Energy Consumption	kWh/a	893

Indoor Data

Air Flow	High - Low	l/s	153 - 75
	High - Low	m3/h	552 - 270
Sound	Pressure High - Low	dB(A)	40 - 24
	Power High - Low	dB(A)	55 - 39
Unit	Height x Width x Depth	mm	600 x 700 x 220
	Weight	kg	16
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8" - 1/4"
	Drain Pipe Connection OD/ID	mm	16/14
Remote controller			WH-TA12LE

Accessories

RB-1301-E	Refrigerant Leak detection sensor
RB-N106S-G	Wireless adapter with Cable

*All [Accessories / Controls](#)

Related Items:

- [BIM Files](#)
- [CAD Files](#)
- [Full Specification](#)
- [Airflow/ Fan Curve](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Installation Manual](#)
- [Owners Manual](#)

