


## VRF 1-WAY STANDARD CASSETTE: MMU - UP0151SH-E

- Quiet operation ONLY 33dB (A).
- Flexible control options, hard wired or infra-red.
- Suitable for small areas, such as hotels, offices and reception rooms.
- Water condensate drain pump lifts condensate water up to 350mm.
- Optional front air discharge duct, allowing the air to be blown horizontally into the room.



Hi - Res Image 



### Performance Data

Capacity Code		HP	1.7
Nominal	Cooling Capacity	kW	4.5
	Heating Capacity	kW	5.0
UK	Cooling Total/Sensible	kW	4.1/3.0
	Heating	kW	3.4
Electrical	Power Input	kW	0.042
	Run Current	Amps	0.34
	Start Current	Amps	0.51

### Indoor Data

Airflow	High - Medium - Low	l/s	208 - 192 - 175
	High - Medium - Low	m <sup>3</sup> /h	750 - 690 - 630
Sound	Pressure High - Medium - Low	dB(A)	37 - 35 - 32
	Power High - Medium - Low	dB(A)	52 - 50 - 47
Unit	Height x Width x Depth	mm	200 x 1000 x 710
	Weight	kg	21
Panel	Type	RBC-	US21PGE
	Height x Width x Depth	mm	20 x 1230 x 800
	Weight	kg	5.5
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	32/25
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

### Accessories

<a href="#">RBC-AMTU31-E</a>	Standard Remote Controller - Full control including service functions
<a href="#">RBC-ASCU11-E</a>	Compact Remote Controller - Includes timer off, back light display, multilingual
<a href="#">RBC-AWSU52-E</a>	Premium Controller - Includes timer and back light display, multilingual (inc. Bluetooth)
<a href="#">RBC-MTSC1</a>	Mini Touch Screen Controller - with configurable icons for indoor units
<a href="#">RBC-MTSC2</a>	Mini Touch Screen Controller - with Schedule Timer, configurable icons for indoor units
<a href="#">TCB-FF101URE2</a>	Auxiliary fresh air flange - For easy fresh air intake using knock out hole of indoor unit.
<a href="#">TCB-BUS21HW-E</a>	Front air discharge unit - Allowing air to be blown horizontally into the room.

### \*All Accessories / Controls

Compatible R410a outdoor condensers:

[Mini SMMS-e](#), [SMMS-u](#), [SHRM-e](#)

Compatible R32 outdoor condensers:

[Mini SMMS](#), [SHRM-a](#)

Related items:

- [Full specification](#)
- [BIM files](#)
- [Airflow/ fan curve](#)
- [Dimensional drawing](#)
- [Wiring diagram](#)
- [Noise curve data](#)
- [Installation manual](#)

