


VRF 4-WAY STANDARD CASSETTE: MMU - UP0121HP-E

- Possible to set three different swing modes.
- Optimal air diffusion up to 4.6m ceiling height.
- Lightweight unit, for easy and quick installation.
- Compact chassis with only 256mm height (up to size 30).
- Self-cleaning function and Ag-ion tip for anti-mould in drain cap.



Hi - Res Image 



Performance Data

| Capacity Code | | HP | 1.3 |
|---------------|------------------------|------|---------|
| Nominal | Cooling Capacity | kW | 3.6 |
| | Heating Capacity | kW | 4.0 |
| UK | Cooling Total/Sensible | kW | 3.3/2.5 |
| | Heating | kW | 2.7 |
| Electrical | Power Input | kW | 0.021 |
| | Run Current | Amps | 0.23 |
| | Start Current | Amps | 0.30 |

Indoor Data

| | | | |
|-----------------|----------------------------------|-----------|-----------------|
| Airflow | High - Medium - Low | l/s | 222 - 203 - 188 |
| | High - Medium - Low | m3/h | 800 - 730 - 680 |
| Sound | Pressure High - Medium - Low | dB(A) | 30 - 29 - 27 |
| | Power High - Medium - Low | dB(A) | 45 - 44 - 42 |
| Unit | Height x Width x Depth | mm | 256 x 840 x 840 |
| | Weight | kg | 20 |
| Panel | Height x Width x Depth | mm | 30 x 950 x 950 |
| | Weight RBC-U32PGP-E | kg | 4 |
| Pipe Connection | Flare Connections (gas - liquid) | inch | 3/8 - 1/4 |
| | Drain Pipe Connection OD/ID | mm | 32/25 |
| Power Supply | Suggested Fuse Size | V/ph/Hz-A | 220-240/1/50-5 |

Accessories

| | |
|--------------------------------|-------------------------------------------------------------------------------------------|
| RBC-AMTU31-E | Standard Remote Controller - Full control including service functions |
| RBC-ASCU11-E | Compact Remote Controller - Includes timer off, back light display, multilingual |
| RBC-AWSU52-E | Premium Controller - Includes timer and back light display, multilingual (inc. Bluetooth) |
| RBC-MTSC1 | Mini Touch Screen Controller - with configurable icons for indoor units |
| RBC-MTSC2 | Mini Touch Screen Controller - with Schedule Timer, configurable icons for indoor units |
| TCB-GFC1603U-E | Fresh Air Chamber - Fresh Air chamber for use with TCB-GB1602UE |
| TCB-BC1602UE | Air discharge direction kit - Air Discharge kit - With 6-direction patterns |
| TCB-FF101URE2 | Auxiliary fresh air flange - For easy fresh air intake by using knock out hole of indoor. |

*All [Accessories](#) / [Controls](#)

Compatible R410a outdoor condensers:

[Mini SMMS-e](#), [SMMS-u](#), [SHRM-e](#)

Compatible R32 outdoor condensers:

[Mini SMMS](#), [SHRM-a](#)

Related items:

- [Full specification](#)
- [BIM files](#)
- [Airflow/ fan curve](#)
- [Dimensional drawing](#)
- [Wiring diagram](#)
- [Noise curve data](#)
- [Installation manual](#)

