


## VRF CEILING SUSPENDED: MMC - UP0271HP-E

- High air flow distance up to 8m.
- Low noise levels, thanks to high diameter fan and DC motor.
- Self-cleaning function, enables the air flow to remain constant.
- Suited for a wide range of applications, but particularly refurbishment projects.
- Optimum louvre control: air flow angle is automatically set to cooling or heating needs.



Hi - Res Image 



### Performance Data

Capacity Code		HP	3.0
Nominal	Cooling Capacity	kW	8
	Heating Capacity	kW	9
UK	Cooling Total/Sensible	kW	7.3/5.3
	Heating	kW	6.1
Electrical	Power Input	kW	0.067
	Run Current	Amps	0.68
	Start Current	Amps	0.97

### Indoor Data

Airflow	High - Medium - Low	l/s	400 - 283 - 217
	High - Medium - Low	m3/h	1440 - 1020 - 750
Sound	Pressure High - Medium - Low	dB(A)	41 - 36 - 29
	Power High - Medium - Low	dB(A)	56 - 51 - 44
Unit	Height x Width x Depth	mm	235 x 1270 x 690
	Weight	kg	30
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	26/20
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

### Accessories

<a href="#">RBC-AMTU31-E</a>	Standard Remote Controller - Full control including service functions
<a href="#">RBC-ASCU11-E</a>	Compact Remote Controller - Includes timer off, back light display, multilingual
<a href="#">RBC-AWSU52-E</a>	Premium Controller - Includes timer and back light display, multilingual (inc. Bluetooth)
<a href="#">RBC-MTSC1</a>	Mini Touch Screen Controller - with configurable icons for indoor units
<a href="#">RBC-MTSC2</a>	Mini Touch Screen Controller - with Schedule Timer, configurable icons for indoor units
<a href="#">RBC-AXU31C-E</a>	Wireless Remote Controller Kit - For use with 0151 to 0561
<a href="#">TCB-DP31CE</a>	Drain pump kit - Antibacterial glass built into drain pump - For use with 0151 to 0561
<a href="#">TCB-KP24CPE</a>	Elbow piping kit - (Required with drain pump kit)

\*All [Accessories](#) / [Controls](#)

Compatible R410a outdoor condensers:

**[Mini SMMS-e](#), [SMMS-u](#), [SHRM-e](#)**

Compatible R32 outdoor condensers:

**[Mini SMMS](#), [SHRM-a](#)**

Related items:

- [Full specification](#)
- [BIM files](#)
- [Airflow/ fan curve](#)
- [Dimensional drawing](#)
- [Wiring diagram](#)
- [Noise curve data](#)
- [Installation manual](#)

