

VRF CONCEALED CHASSIS: MML - UP0241BH-E

- Ideal for office and other commercial buildings.
- Fits perfectly for specialist applications such as a library or hospital building.
- Removable split front panel with immediate access to the main components.
- Compact design, which can be installed under a window sill, that is only 600mm in height.
- Depth of only 220mm, the unit can be installed along the wall ensuring maximum space saving.



Hi - Res Image



Performance Data

Capacity Code		HP	2.5
Nominal	Cooling Capacity	kW	7.1
	Heating Capacity	kW	8.0
UK	Cooling Total/Sensible	kW	6.4/4.2
	Heating	kW	5.4
Electrical	Power Input	kW	0.110
	Run Current	Amps	0.51
	Start Current	Amps	1.00

Indoor Data

Airflow	High - Medium - Low	l/s	264 - 219 - 178
	High - Medium - Low	m3/h	950 - 790 - 640
External Static Pressure	Standard	Pa	5
Sound	Pressure High - Medium - Low	dB(A)	42 - 37 - 33
	Power High - Medium - Low	dB(A)	57 - 52 - 48
Unit	Height x Width x Depth	mm	600 x 1045 x 220
	Weight	kg	28
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8
	Drain Pipe Connection ID	mm	20
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5

Accessories

RBC-AMTU31-E	Standard Remote Controller - Full control including service functions
RBC-ASCU11-E	Compact Remote Controller - Includes timer off, back light display, multilingual
RBC-AMSU51-E	Standard Remote Controller - Includes timer off, back light display, multilingual
RBC-AWSU52-E	Premium Controller - Includes timer and back light display, multilingual (inc. Bluetooth)
RBC-MTSC1	Mini Touch Screen Controller - with configurable icons for indoor units
RBC-MTSC2	Mini Touch Screen Controller - with Schedule Timer, configurable icons for indoor units

*All [Accessories](#) / [Controls](#)

Compatible R410a outdoor condensers:

[Mini SMMS-e](#), [SMMS-u](#), [SHRM-e](#)

Compatible R32 outdoor condensers:

[Mini SMMS](#), [SHRM-a](#)

Related items:

- [Full specification](#)
- [BIM files](#)
- [Dimensional drawing](#)
- [Wiring diagram](#)
- [Noise curve data](#)
- [Installation manual](#)

