

SEIYA: RAS - B13S4KVG-E

- A++ in both Heating and cooling.
- Power supply to indoor or outdoor unit.
- Sleek and compact suitable for all applications.
- Available in both single and multi split applications.
- Compatible with WI-FI with adapter in the box as standard.



Retail Price (interactive icons):



UK



ROI



Hi - Res Image 

ENTRY TIER PRODUCT RANGE

Performance			
Indoor Unit		RAS-	B13S4KVG-E
Outdoor Unit		RAS-	13E2AVG-E
Nominal	Cooling Capacity	kW	3.3
	Heating Capacity	kW	3.6
	EER/COP	W/W	3.30/4.14
UK	Cooling Total/Sensible	kW	3.22/2.49
	Heating	kW	2.20
Cooling EN14825	Range Min. - Max.	kW	1.20 - 3.60
	Power Input	kW	1.00
	Pdesign	kW	3.3
	SEER/Energy Efficiency Class		7.00/A++
	Seasonal Energy Consumption	kWh/a	165
Heating EN14825	Range Min. - Max.	kW	0.97 - 4.50
	Power Input	kW	0.87
	Pdesign	kW	2.7
	SCOP/Energy Efficiency Class		4.60/A++
	Seasonal Energy Consumption	kWh/a	822

Indoor Data			
Air Flow	High - Low	l/s	208 - 92
	High - Low	m3/h	750 - 330
Sound	Pressure High - Low	dB(A)	42 - 21
	Power High - Low	dB(A)	54
Unit	Height x Width x Depth	mm	293 x 798 x 230
	Weight	kg	9
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8" - 1/4"
	Drain Pipe Connection OD/ID	mm	16/14
Remote controller			WH-TG01NE

Accessories	
RB-RXS33-E	Option Remote Controller (Weekly Timer)
RB-RXS34-E	Option Black remote

*All [Accessories / Controls](#)

Related Items:

- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Airflow/ Fan Curve](#)
- [Installation Manual](#)
- [Owners Manual](#)

