

SEIYA: RAS - B16S4KVG-E

- A++ in both Heating and cooling.
- Power supply to indoor or outdoor unit.
- Sleek and compact suitable for all applications.
- Available in both single and multi split applications.
- Compatible with Wi-Fi with adapter in the box as standard.



Retail Price (interactive icons):



UK



ROI



Hi - Res Image 

ENTRY TIER PRODUCT RANGE

Performance			
Indoor Unit		RAS-	B16S4KVG-E
Outdoor Unit		RAS-	16E2AVG-E
Nominal	Cooling Capacity	kW	4.2
	Heating Capacity	kW	5.0
	EER/COP	W/W	3.31/3.73
UK	Cooling Total/Sensible	kW	4.49/3.36
	Heating	kW	3.33
Cooling EN14825	Range Min. - Max.	kW	1.40 - 4.70
	Power Input	kW	1.27
	Pdesign	kW	4.2
	SEER/Energy Efficiency Class		7.00/A++
	Seasonal Energy Consumption	kWh/a	210
Heating EN14825	Range Min. - Max.	kW	1.30 - 6.00
	Power Input	kW	1.34
	Pdesign	kW	3.6
	SCOP/Energy Efficiency Class		4.60/A++
	Seasonal Energy Consumption	kWh/a	1095

Indoor Data			
Air Flow	High - Low	l/s	212 - 92
	High - Low	m3/h	760 - 330
Sound	Pressure High - Low	dB(A)	43 - 22
	Power High - Low	dB(A)	56
Unit	Height x Width x Depth	mm	293 x 798 x 230
	Weight	kg	9
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2" - 1/4"
	Drain Pipe Connection OD/ID	mm	16/14
Remote controller			WH-TG01NE

Accessories

RB-RXS33-E	Option Remote Controller (Weekly Timer)
RB-RXS34-E	Option Black remote

*All [Accessories / Controls](#)

Related Items:

- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Airflow/ Fan Curve](#)
- [Installation Manual](#)
- [Owners Manual](#)

