

- Optional Occupancy sensor.
- Optional wired remote controller.
- Optional Wireless remote controller kit.
- Elegant and unobtrusive with modern design.
- Suited for 600x600 grid ceilings thanks to compact and thin chassis.



Hi - Res Image 



UK



ROI



Indoor Data			
Air Flow	High - Low	l/s	172 - 119
	High - Low	m3/h	620 - 470
Sound	Pressure High - Low	dB(A)	39 - 33
	Power High - Low	dB(A)	52 - 46
Unit	Height x Width x Depth	mm	256 x 575 x 575
	Weight	kg	16
Panel RBC-UM21P-E	Height x Width x Depth	mm	12 x 620 x 620
	Weight	kg	3
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4
	Drain Pipe Connection OD/ID	mm	32/25

<u>RBC-AXU31UMP-E</u>	Wireless remote controller Kit
<u>RBC-AMSU52-E</u>	Wired Remote Controller
<u>TCB-SIR41UM-E</u>	Occupancy sensor

Related Items:

- [BIM Files](#)
- [CAD Files](#)
- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Airflow/ Fan Curve](#)
- [Noise Curve Data](#)
- [Installation Manual](#)
- [Owners Manual](#)

