

## VRF FLOOR MOUNTED CONSOLE: MML - UP0151H-E

- One single cabinet size, for all capacity models.
- Minimum space required for installation and servicing.
- Refrigerant and drain piping with four installation possibilities.
- Has the ability to have Air flow in horizontal and vertical direction.
- Perfect choice, for refurbishment projects, where the available space is limited.



Hi - Res Image 

## Performance Data

|               |                        |      |         |
|---------------|------------------------|------|---------|
| Capacity Code |                        | HP   | 1.7     |
| Nominal       | Cooling Capacity       | kW   | 4.5     |
|               | Heating Capacity       | kW   | 5.0     |
| UK            | Cooling Total/Sensible | kW   | 3.8/2.5 |
|               | Heating                | kW   | 3.4     |
| Electrical    | Power Input            | kW   | 0.092   |
|               | Run Current            | Amps | 0.43    |
|               | Start Current          | Amps | 0.80    |

## Indoor Data

|                 |                                  |           |                 |
|-----------------|----------------------------------|-----------|-----------------|
| Airflow         | High - Medium - Low              | l/s       | 250 - 217 - 180 |
|                 | High - Medium - Low              | m3/h      | 900 - 780 - 650 |
| Sound           | Pressure High - Medium - Low     | dB(A)     | 45 - 41 - 38    |
|                 | Power High - Medium - Low        | dB(A)     | 60 - 56 - 53    |
| Unit            | Height x Width x Depth           | mm        | 630 x 950 x 230 |
|                 | Weight                           | kg        | 37              |
| Pipe Connection | Flare Connections (gas - liquid) | inch      | 1/2 - 1/4       |
|                 | Drain Pipe Connection OD/ID      | mm        | 26/20           |
| Power Supply    | Suggested Fuse Size              | V/ph/Hz-A | 220-240/1/50-5  |

## Accessories

|                              |                                                                                           |
|------------------------------|-------------------------------------------------------------------------------------------|
| <a href="#">RBC-AMTU31-E</a> | Standard Remote Controller - Full control including service functions                     |
| <a href="#">RBC-ASCU11-E</a> | Compact Remote Controller - Includes timer off, back light display, multilingual          |
| <a href="#">RBC-AMSU51-E</a> | Standard Remote Controller - Includes timer off, back light display, multilingual         |
| <a href="#">RBC-AWSU52-E</a> | Premium Controller - Includes timer and back light display, multilingual (inc. Bluetooth) |
| <a href="#">RBC-MTSC1</a>    | Mini Touch Screen Controller - with configurable icons for indoor units                   |
| <a href="#">RBC-MTSC2</a>    | Mini Touch Screen Controller - with Schedule Timer, configurable icons for indoor units   |
| <a href="#">RBC-AXU31-E</a>  | Wireless Receiver Kit - Compatible with all model sizes                                   |

\*All [Accessories](#) / [Controls](#)

Compatible R410a outdoor condensers:

### Mini SMMS-e, SMMS-u, SHRM-e

Compatible R32 outdoor condensers:

### Mini SMMS, SHRM-a

Related items:

- [Full specification](#)
- [BIM files](#)
- [CAD files](#)
- [Airflow/ fan curve](#)
- [Dimensional drawing](#)
- [Wiring diagram](#)
- [Noise curve data](#)
- [Installation manual](#)

