

## RAV - Digital Inverter - Standard 4-Way Cassette - 561 & 801 - 1ph

- Built-in high-lift drain pump
- Individual setting of louvre position
- Self-cleaning function and Ag-ion tip
- Compatible with Wi-Fi when utilising adapter
- Compact light weight chassis for easy installation



Hi - Res Image



Retail Price (interactive icons):



### STANDARD PRODUCT RANGE

Performance				
Indoor Unit		RAV-	HM561UTP-E	HM801UTP-E
Outdoor Unit		RAV-	<a href="#">GM561ATP-E1</a>	<a href="#">GM801ATP-E</a>
Nominal	Cooling Capacity	kW	5.0	6.7
	Heating Capacity	kW	5.3	7.7
	EER/COP	W/W	3.21/3.90	3.02/3.62
UK	Cooling Total/Sensible	kW	4.80/3.60	6.40/4.80
	Heating	kW	3.79	5.51
Cooling EN14825	Range Min. - Max.	kW	1.5 - 5.6	1.5 - 8.0
	Power Input	kW	1.56	2.22
	Pdesign	kW	5.0	6.7
	SEER/Energy Efficiency Class		6.34/A++	5.81/A+
	Seasonal Energy Consumption	kWh/a	276	403
Heating EN14825	Range Min. - Max.	kW	1.5 - 6.3	1.5 - 9.0
	Power Input	kW	1.36	2.13
	Pdesign	kW	2.8	5.1
	SCOP/Energy Efficiency Class		4.60/A++	4.42/A+
	Seasonal Energy Consumption	kWh/a	852	1615

Indoor Data				
Air Flow	High - Medium - Low	l/s	292 - 242 - 217	342 - 267 - 225
	High - Medium - Low	m3/h	1050 - 870 - 780	1230 - 960 - 810
Sound	Pressure High - Medium - Low	dB(A)	32 - 29 - 28	35 - 31 - 28
	Power High - Medium - Low	dB(A)	47 - 44 - 43	50 - 46 - 43
Unit	Height x Width x Depth	mm	256 x 840 x 840	256 x 840 x 840
	Weight	kg	20	20
Panel	Height x Width x Depth	mm	30 x 950 x 950	30 x 950 x 950
	Weight RBC-U33P-E	kg	4.2	4.2
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	VP32/25	VP32/25

[Full Specification](#)

[Full Specification](#)

### Accessories

<a href="#">RBC-ASCU32Y-E</a>	Compact Controller - Local Compact Controller , LCD Display
<a href="#">RBC-AMTU31-E</a>	Standard Controller - Standard remote controller can control an individual indoor unit or a group of 8 indoor units.
<a href="#">RBC-AMSU52-E</a>	Standard Controller - Includes timer and backlight display as well as power-save functions, multilingual
<a href="#">RBC-AWSU52-E</a>	Premium Remote Controller - Includes timer and backlight display as well as power-save functions, multilingual (inc. Bluetooth)
RBC-U33PB-E	Ceiling Panel (Black) - Universal for all model sizes
<a href="#">RBC-AXU33UP-E</a>	Remote Controller - Wireless Receiver Kit for 4-Way Cassette (White)
<a href="#">RBC-AXU33UPB-E</a>	Remote Controller - Wireless Receiver Kit for 4-Way Cassette (Black)

### Related items:

- [BIM files](#)
- [CAD files](#)
- [Airflow/ fan curve](#)
- [Dimensional drawing - 561 / 801](#)
- [Wiring diagram](#)
- [Noise curve data](#)
- [Installation manual](#)

