

RAV - Digital Inverter - Slim Ducted - 561 - 1ph

- New TU2C-link protocol
- Ultra thin chassis design (210mm)
- New compact and lightweight chassis
- Improved external static pressure up to 50pa
- Quiet operation with lower sound pressure levels 29db(a)



Retail Price (interactive icons):



Hi - Res Image 

STANDARD PRODUCT RANGE

Performance			
Indoor Unit		RAV-	HM561SDTY-E
Outdoor Unit		RAV-	GM561ATP-E1
Nominal	Cooling Capacity	kW	5.0
	Heating Capacity	kW	5.3
	EER/COP	W/W	2.69/3.53
UK	Cooling Total/Sensible	kW	4.80/3.30
	Heating	kW	3.79
Cooling EN14825	Range Min. - Max.	kW	1.5 - 5.6
	Power Input	kW	1.86
	Pdesign	kW	5.0
	SEER/Energy Efficiency Class		5.68/A+
	Seasonal Energy Consumption	kWh/a	308
Heating EN14825	Range Min. - Max.	kW	1.5 - 6.3
	Power Input	kW	1.50
	Pdesign	kW	2.8
	SCOP/Energy Efficiency Class		4.00/A+
	Seasonal Energy Consumption	kWh/a	980

Indoor Data			
Air Flow	High - Medium - Low	l/s	216 - 198 - 180
	High - Medium - Low	m3/h	780 - 715 - 650
External Static Pressure	Standard (Upper - Lower)	Pa	30 (50-10)
Sound	Pressure High - Medium - Low	dB(A)	34 - 32 - 29
	Power High - Medium - Low	dB(A)	56 - 54 - 51
Unit	Height x Width x Depth	mm	210 x 900 x 450
	Weight	kg	19
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4
	Drain Port Connection Upper - Lower	mm	VP25 - VP25
	Lift Pump Drain Height from Unit Base		< 850

Accessories

RBC-ASCU32Y-E	Compact Controller - Local Compact Controller , LCD Display
RBC-AMTU31-E	Remote Controller - Includes timer and back light display as well as power-save functions, multilingual
RBC-AMSU52-E	Remote Controller - Includes timer and back light display as well as power-save functions, multilingual
RBC-AWSU52-E	Premium Remote Controller - Includes timer and back light display as well as power-save functions, multilingual (inc. Bluetooth)

Related items:

- [BIM files](#)
- [CAD files](#)
- [Airflow/ fan curve](#)
- [Dimensional drawing](#)
- [Wiring diagram](#)
- [Noise curve data](#)
- [Installation manual](#)

