

RAV - Digital Inverter - Outdoor Units - 2241 & 2801 - 3ph

- High SEER/SCOP energy efficiencies.
- 19% lower in weight versus previous models
- 100m maximum pipe length for flexible installation
- Compact single fan chassis for easy installation and transportation.
- Expansion of Indoor unit combinations with 4HP High Wall twin connection.



Retail Price (interactive icons):



Hi - Res Image

STANDARD PRODUCT RANGE

Performance		STANDARD PRODUCT RANGE		
Outdoor Unit		RAV	GM2241AT8-E1	GM2801AT8-E1
Operating Range	Cooling	C°	-15 to 46	-15 to 46
	Heating		-27 to 15	-27 to 15
Air Flow	High	m ³ /h - l/s	9150- 2541	10890- 3025
Sound	Pressure High Cooling/Heating	dB(A)	58 - 60	61 - 63
	Power High Cooling/Heating	dB(A)	76 - 76	78 - 80
Unit	Height x Width x Depth	mm	1550 x 1010 x 370	1550 x 1010 x 370
	Weight	kg	142	142
Pipe Connection	Flare Connections (gas - liquid)	inch	1 1/8 - 1/2	1 1/8 - 1/2
	Min.-Max. Length	m	5-100	5-100
	Maximum Height Difference	m	±30	±30
	Drain Port Connection	mm	16	16
Refrigerant Charge	Gas - Base Charge/Chargeless Length	m	R32 - 5.0	R32 - 5.0
	Additional Charge Liquid Side	g/m	20	40
Run Current	Maximum	Amps	10.15	14.49
Power Cable	Outdoor to Indoor		3 core + earth	3 core + earth
Power Supply	Suggested Fuse Size	V/ph/Hz-A	380-415/3/50-16	380-415/3/50-20

Related items:

- [BIM files](#)
- [CAD files](#)
- [Refrigerant cycle diagram](#)
- [Dimensional drawing](#)
- [Wiring diagram](#)
- [Noise curve data](#)
- [Installation manual](#)

