

RAV - Super Digital Inverter - Outdoor Units 1101 1ph & 3ph

- Quiet operation as low as 33dB (A)
- Ability to operate down to a 10% load
- Precise capacity control at all conditions
- Standby power consumption reduced by 50% to 6W
- Wide ambient range: cooling -15°C to +52°C heating +15°C to -27°C



Retail Price (interactive icons):



Hi - Res Image

HIGH TIER PRODUCT RANGE

Performance		HIGH TIER PRODUCT RANGE		
Outdoor Unit		RAV	GP1101AT-E	GP1101AT8-E
Operating Range	Cooling	C°	-15 to 52	-15 to 46
	Heating		-27 to 15	-20 to 15
Air Flow	High	m ³ /h - l/s	6960 - 1933	6060 - 1683
Sound	Pressure High Cooling/Heating	dB(A)	49 - 50	49 - 50
	Power High Cooling/Heating	dB(A)	66 - 67	66 - 67
Unit	Height x Width x Depth	mm	1550 x 1010 x 370	1340 x 900 x 320
	Weight	kg	104	95
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8	5/8 - 3/8
	Min.-Max. Length	m	3-75	3 - 75
	Maximum Height Difference	m	±30	±30
	Drain Port Connection	mm	16	16
Refrigerant R32	Base Charge/Chargeless Length	m	R32 - 3.1/30	2.6/30
	Additional Charge Liquid Side	g/m	35	35
Run Current	Maximum	Amps	11.20	4.52
Power Cable	Outdoor to Indoor		3 core + earth	3 core + earth
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-20	380-415/3/50-10

Related items:

- [BIM files](#)
- [CAD files 1ph & 3ph](#)
- [Refrigerant cycle diagram](#)
- [Dimensional drawing](#)
- [Wiring diagram 1ph & 3ph](#)
- [Noise curve data 1ph & 3ph](#)
- [Installation manual 1ph & 3ph](#)

