

## RAV - Super Digital Inverter - Outdoor Units 561 & 801

- Quiet operation as low as 33dB (A)
- Ability to operate down to a 10% load
- Precise capacity control at all conditions
- Standby power consumption reduced by 50% to 6W
- Wide ambient range: cooling -15°C to +52°C heating +15°C to -27°C



Hi - Res Image



Retail Price (interactive icons):



### HIGH TIER PRODUCT RANGE

Performance		HIGH TIER PRODUCT RANGE		
Outdoor Unit		RAV	GP561ATW-E	GP801ATW-E
Operating Range	Cooling	C°	-15 to 52	-15 to 52
	Heating		-27 to 15	-27 to 15
Air Flow	High	m <sup>3</sup> /h - l/s	2250 - 625	3180 - 883
Sound	Pressure High Cooling/Heating	dB(A)	46 - 48	46 - 48
	Power High Cooling/Heating	dB(A)	63 - 65	63 - 65
Unit	Height x Width x Depth	mm	630 x 799 x 299	1050 x 1010 x 370
	Weight	kg	45	74
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4	5/8 - 3/8
	Min.-Max. Length	m	3 - 50	3 - 50
	Maximum Height Difference	m	±30	±30
	Drain Port Connection	mm	16	16
Refrigerant R32	Base Charge/Chargeless Length	m	1.35/20	1.9/30
	Additional Charge Liquid Side	g/m	20	35
Run Current	Maximum	Amps	6.13	0.88
Power Cable	Outdoor to Indoor		3 core + earth	3 core + earth
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-16	220-240/1/50-16

### Related items:

- BIM files [561](#) & [801](#)
- CAD files [561](#) & [801](#)
- [Refrigerant cycle diagram](#)
- [Dimensional drawing](#)
- [Wiring diagram](#)
- [Noise curve data](#)
- Installation manual [561](#) & [801](#)

