



Note: Allow additional 40Pa. For ePM2.5 (F7) Filter (if selected)

VHR-CF 260 Airflow (l/s) vs Resistance (Pa)						
Selection	0	50	100	150	200	Voltage
Curve 1	280	260	236	212	186	5.0
Curve 2	303	284	260	234	210	6.0
Curve 3	330	308	286	260	234	7.0
Curve 4	357	333	310	285	260	8.0

VHR-CF260 In-Duct Sound Power Data dB (Ref. 10 ₁₂ W)										
		63	125	250	500	1k	2k	4k	8k	Breakout @3m (dBA)
Curve 1	S.A. / E.A.	56	60	60	55	55	55	48	44	28
Curve 1	F.A. / R.A.	54	58	58	53	53	53	46	42	
Curve 2	S.A. / E.A.	58	63	63	58	59	60	51	46	30
Curve 2	F.A. / R.A.	56	61	61	56	57	58	49	44	
Curve 3	S.A. / E.A.	60	65	63	62	63	62	56	54	33
Curve 3	F.A. / R.A.	57	62	60	59	60	59	53	51	
Curve 4	S.A. / E.A.	61	65	64	60	61	62	54	50	35
Curve 4	F.A. / R.A.	59	63	62	58	59	60	52	48	