

RAV - Digital Inverter - High Wall - 561 & 701 - 1ph

- Enhanced filtration system
- Optimum and uniform air distribution
- Compatible with WI-FI when utilising adapter
- Sleek and compact suitable for all applications
- Self-cleaning feature to prevent mould formation



Retail Price (interactive icons):

UK



ROI



Hi - Res Image



Supporting resources, including BIM & CAD files, technical drawings, manuals and product documentation, are available in the Related Items section below.

STANDARD PRODUCT RANGE

Performance				
Indoor Unit		RAV-	HM561KRTP-E	HM701KRTP-E
Outdoor Unit		RAV-	GM563ATP-E	GM703ATP-E
Nominal	Cooling Capacity	kW	5.0	6.1
	Heating Capacity	kW	5.3	7.0
	EER/COP	W/W	3.42 / 3.90	3.28 / 3.32
UK	Cooling Total/Sensible	kW	4.88 / 4.41	5.96 / 4.66
	Heating	kW	3.47	4.60
Cooling EN14825	Range Min. - Max.	kW	1.5 - 5.6	1.7 - 6.5
	Power Input	kW	1.46	1.86
	Pdesign	kW	5.0	6.1
	SEER/Energy Efficiency Class		6.69 / A++	6.53 / A++
	Seasonal Energy Consumption	kWh/a	262	327
Heating EN14825	Range Min. - Max.	kW	1.5 - 6.3	1.6 - 7.5
	Power Input	kW	1.36	2.11
	Pdesign	kW	5.3	7.0
	SCOP/Energy Efficiency Class		4.2 / A+	4.1 / A+
	Seasonal Energy Consumption	kWh/a	933	1195

Indoor Data				
Air Flow	High - Medium - Low	l/s	267 - 231 - 189	278 - 242 - 189
	High - Medium - Low	m3/h	960 - 830 - 680	1000 - 870 - 680
Sound	Pressure High - Medium - Low	dB(A)	42 - 39 - 36	44 - 40 - 35
	Power High - Medium - Low	dB(A)	57 - 54 - 51	59 - 55 - 50
Unit	Height x Width x Depth	mm	320 x 1050 x 250	320 x 1050 x 250
	Weight	kg	14	14
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	VP16/14	VP16/14
Remote controller			WH-TA09NE	
			Full Specification	Full Specification

Accessories	
RBC-ASCU32Y-E	Compact Controller - Local Compact Controller , LCD Display
RBC-AMTU31-E	Standard Controller - Standard remote controller can control an individual indoor unit or a group of 8 indoor units.
RBC-AMSU52-E	Standard Controller - Includes timer and back light display as well as power-save functions, multilingual
RBC-AWSU52-E	Premium Remote Controller - Includes timer and back light display as well as power-save functions, multilingual (inc. Bluetooth)

Related items:

- [BIM files](#)
- [CAD files](#)
- [Airflow/ fan curve - 561 / 701](#)
- [Dimensional drawing - 561 / 701](#)
- [Wiring diagram - 561 / 701](#)
- [Noise curve data - 561 / 701](#)
- [Data book](#)
- [Installation manual](#)

