

RAV - Digital Inverter - Standard 4-Way Cassette - 561 & 701 - 1ph

- Built-in high-lift drain pump
- Individual setting of louvre position
- Self-cleaning function and Ag-ion tip
- Compatible with Wi-Fi when utilising adapter
- Compact light weight chassis for easy installation



Retail Price (interactive icons):



Hi - Res Image

Supporting resources, including BIM & CAD files, technical drawings, manuals and product documentation, are available in the Related Items section below.

STANDARD PRODUCT RANGE				
Performance				
Indoor Unit		RAV-	HM561UTP-E	HM701UTP-E
Outdoor Unit		RAV-	GM563ATP-E	GM703ATP-E
Nominal	Cooling Capacity	kW	5.0	6.1
	Heating Capacity	kW	5.3	7.0
	EER/COP	W/W	3.57 / 4.08	3.60 / 3.91
UK	Cooling Total/Sensible	kW	4.88 / 4.16	5.96 / 4.84
	Heating	kW	3.47	4.62
Cooling EN14825	Range Min. - Max.	kW	1.5 - 5.6	1.5 - 6.5
	Power Input	kW	1.40	1.69
	Pdesign	kW	5.0	6.1
	SEER/Energy Efficiency Class		6.84 / A++	6.80 / A++
	Seasonal Energy Consumption	kWh/a	256	314
Heating EN14825	Range Min. - Max.	kW	1.5 - 6.3	1.6 - 7.5
	Power Input	kW	1.30	1.79
	Pdesign	kW	2.8	3.5
	SCOP/Energy Efficiency Class		4.62 / A++	4.80 / A++
	Seasonal Energy Consumption	kWh/a	848	1021
Indoor Data				
Air Flow	High - Medium - Low	l/s	292 - 242 - 217	317 - 254 - 221
	High - Medium - Low	m3/h	1050 - 870 - 780	1140 - 915 - 795
Sound	Pressure High - Medium - Low	dB(A)	32 - 29 - 28	34 - 30 - 28
	Power High - Medium - Low	dB(A)	47 - 44 - 43	49 - 45 - 43
Unit	Height x Width x Depth	mm	256 x 840 x 840	256 x 840 x 840
	Weight	kg	20	20
Panel	Height x Width x Depth	mm	30 x 950 x 950	30 x 950 x 950
	Weight RBC-U33P-E	kg	4.2	4.2
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	VP32/25	VP32/25
			Full Specification	Full Specification

Accessories	
RBC-ASCU32Y-E	Compact Controller - Local Compact Controller , LCD Display
RBC-AMTU31-E	Standard Controller - Standard remote controller can control an individual indoor unit or a group of 8 indoor units.
RBC-AMSU52-E	Standard Controller - Includes timer and backlight display as well as power-save functions, multilingual
RBC-AWSU52-E	Premium Remote Controller - Includes timer and backlight display as well as power-save functions, multilingual (inc. Bluetooth)
RBC-U33PB-E	Ceiling Panel (Black) - Universal for all model sizes
RBC-AXU33UP-E	Remote Controller - Wireless Receiver Kit for 4-Way Cassette (White)
RBC-AXU33UPB-E	Remote Controller - Wireless Receiver Kit for 4-Way Cassette (Black)

Related items:

- [BIM files](#)
- [CAD files](#)
- [Airflow/ fan curve](#)
- [Dimensional drawing](#)
- [Wiring diagram_ - 561 / 701](#)
- [Noise curve data - 561 / 701](#)
- [Data book](#)
- [Installation manual](#)

